


TECHNICAL DATA					
DESIGN					
DESIGN STANDARD	BS/EN12953				
CAPACITY (kcal/hr)	700,000				
WORKING PRESSURE (bar)					
CORROSION ALLOWANCE	0.75 (mm)				
MATERIAL					
SHELL & FURNACE	17Mn-4 (DIN 17155)				
TUBE SHEETS	17Mn-4 (DIN 17155)				
FIRE TUBES	St 35.8 (DIN 17175)				
FLANGES	FORGED STEEL ASME B.16.5-150				
INSPECTION					
PENETRATION TEST	YES				
ULTRASONIC TEST	YES				
HYDROSTATIC TEST	YES				
CONNECTIONS SIZE					
WATER RETURN	K	3"			
WATER OUTLET	L	3"			
SAFETY	M	1 1/4"			
EXPANSION	N	1 1/4"			
DRAIN	O	1"			
STACK Temp. Sensor	Q	1/2"			
TEMPERATURE SENSOR	R	1/2"			
STACK I.D	S	12"			
CONTROLLER	U	1/2"			
VENT	V	1"			
HAND HOLE	T	80			
SKID I-BEAM SIZE(IPN)	I	140			
GENERAL NOTE					
1- ALL DIMENSIONS & ELEVATIONS ARE IN mm.					
2-THE MAP CONTAINS THE CONSTRUCTION TOLERANCES					
3-THE MAP PROVIDED IS NOT SCALED. SCALED MAP IS PROVIDED UPON REQUEST.					
TITLE: REVERSE FLAME BOILER DIMENSION DRAWING					
DRAFTED	CHECKED	APPROVED	CONFIRMED	REV.	SCALE
				R02	NTS
VENDOR:					
 PACKMAN Industrial Group					

